



## LED Strip

| Art. Number   | Description                               |
|---|---|
| <p data-bbox="316 590 462 621"><b>BC-T8-600</b></p>      | Power: 10W                                |
|   | Voltage : AC85-264V                       |
|   | Luminous Flux: 750-850LM                  |
|   | Color.T: 2800-3200K;4000-4500K;6000-6500K |
|   | LED QTY: 90LEDs 3014SMD                   |
|   | Beam Angle: 120°                          |
|   | Power type: non-isolated Power supply     |
|   | IP Rate: IP 54                            |
|   | Base:G13 rotatable / G13 non rotatable    |
|   | Length: 600mm                             |
| Art. Number   | Description                               |
| <p data-bbox="316 1226 462 1257"><b>BC-T8-600</b></p>  | Power: 10W                                |
|   | Voltage : AC85-264V                       |
|   | Luminous Flux: 750-850LM                  |
|   | Color T:2800-3200K;4000-4500K;6000-6500K  |
|   | LED QTY: 90LEDs 3014SMD                   |
|   | Beam Angle: 120°                          |
|   | IP Rate: IP 54                            |
|   | Power type: isolated Power supply         |
|   | Base:G13 rotatable / G13 non rotatable    |
|   | Length: 600mm                             |
| Art. Number   | Description                               |
| <p data-bbox="316 1843 462 1875"><b>BC-T8-1200</b></p>  | Power: 22W                                |
|   | Voltage: AC85-264V                        |
|   | Luminous Flux: 1500-1600LM                |

|                             | <p><b>Color T:2800-3200K;4000-4500K;6000-6500K</b></p> <p><b>LED QTY: 200LEDs 3014SMD</b></p> <p><b>Beam Angle: 120°</b></p> <p><b>IP Rate: IP 54</b></p> <p><b>Power type: non-isolated Power supply</b></p> <p><b>Base: G13 rotatable / G13 non rotatable</b></p> <p><b>Length: 1200mm</b></p>  |
|--|---|
| Art. Number  | Description   |
| <p><b>BC-T8-1200</b></p>   | <p><b>Power: 22W</b></p> <p><b>Voltage: AC85-264V</b></p> <p><b>Luminous Flux: 1500-1600LM</b></p> <p><b>Color T:2800-3200K;4000-4500K;6000-6500K</b></p> <p><b>LED QTY: 200LEDs 3014SMD</b></p> <p><b>Beam Angle: 120°</b></p> <p><b>IP Rate: IP 54</b></p> <p><b>Power type: isolated Power supply</b></p> <p><b>Base: G13 rotatable / G13 non rotatable</b></p> <p><b>Length: 1200mm</b></p>   |
| Art. Number  | Description   |
| <p><b>BC-T8-1500</b></p>  | <p><b>Power: 26W</b></p> <p><b>Voltage : AC85-264V</b></p> <p><b>Luminous Flux: 2000-2100LM</b></p> <p><b>Color.T: 2800-3200K;4000-4500K;6000-6500K</b></p> <p><b>LED QTY: 240LEDs 3014SMD</b></p> <p><b>Beam Angle: 120°</b></p> <p><b>IP Rate: IP 54</b></p> <p><b>Power type: isolated Power supply</b></p> <p><b>Base: G13 rotatable / G13 non rotatable</b></p> <p><b>Length: 1500mm</b></p> |